



Turn to the experts



UP TO
20 SEER²

MINI SPLIT SYSTEM 40MHHFC / 38MHRFC



MAIN FEATURES:



Self-Cleaning



Self-diagnosis and Auto-protection



Sleep Mode



2-way Draining



Turbo



Louver Position Memory



Auto Restart Function



Timer



Follow me



Golden Anti Corrosion Protection



Wifi Enabled*

*Sold separately Wifi Kit #: 17310900A06281

Capacity			12K CO 115V	12K CO	18K CO	24K CO
Indoor(Carrier model name)			40MHHFC12XA1	40MHHFC12XA3	40MHHFC18XA3	40MHHFC24XA3
Outdoor(Carrier model name)			38MHRFC12AA1	38MHRFC12AA3	38MHRFC18AA3	38MHRFC24AA3
Power supply		V-Ph-Hz	115V,1Ph,60HZ	220-230V,1Ph,60Hz	220-230V,1Ph,60Hz	220-230V,1Ph,60Hz
Cooling (Standard conditions)	Capacity (range)	Btu/hr	12000(3000-13000)	12000(3000-13000)	17000(4700-18000)	22000(5300-24300)
	Input	W	1270(120-1300)	1150(110-1350)	1560(120-1650)	1930(115-2230)
	Current	A	13.0(1.8-15.5)	7.6(1.7-9.8)	6.78(0.5-7.2)	9.0(0.9-9.9)
	EER	Btu/hr/W	9.45	10.43	10.90	11.40
	SEER2	Btu/hr/W	17	17	19	20
Rated Input		W	1800	2000	2950	3000
Rated Current		A	17.0	13.0	13.5	14
Indoor unit	Dimension(W*D*H)	mm	805x194x285	805x194x285	957x213x302	1040x220x327
	Packing (W*D*H)	mm	870x285x360	870x285x360	1035x305x380	1120x405x310
	Net/Gross weight	kg	7.7/10.0	7.7/9.9	10.4/13.3	12.2/15.6
Outdoor unit	Dimension(W*D*H)	mm	720x270x495	720x270x495	765x303x555	805x330x554
	Packing (W*D*H)	mm	842x357x550	842x357x550	885x375x605	940x410x605
	Net/Gross weight	kg	21.5/22.4	20.0/21.9	24.1/26.4	28.2/30.6
Refrigerant type		kg	R32	R32	R32	R32
Refrigerant charge		kg	0.4	0.4	0.62	0.75
Room temperature	Indoor(cooling/ heating)	C	17~32//	17~32//	17~32//	17~32//
	Outdoor(cooling/heating)	C	0~50//	0~50//	0~50//	0~50//



Turn to the experts

REF:082024

Visit www.carrierlatam.com to find your nearest distributor.

 Carrier InterAmerica Corp. |   @carrierlatam